This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Director, Charting and Geodetic Services (N/CG22), National Ocean Service, NOAA, Rockville, Maryland 20852.

CAUTION

For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel.

14836

SOUNDINGS IN FEET

Nautical Chart Catalog No. 4, Panel D

14836



NOTE B

The channel legend reflects the Corps of Engineers project depth. The Corps of Engineers publishes the controlling depth periodically in the U.S. Coast Guard Local Notice to Mariners. For further information on channel depths, direct inquiries to Office of the District Engineer, Corps of Engineers, Buffalo, N.Y.

NATIONAL OCEAN SERVICE

UNITED STATES - GREAT LAKES



UNITED STATES - GREAT LAKES

LAKE ERIE - OHIO

ASHTABULA HARBOR

Polyconic Projection
Scale 1:5,000
North American 1902 Datum
SOUNDINGS IN FEET

NOTES

PLANE OF REFERENCE OF THIS CHART (Low Water Datum) .... 568.6 ft. Referred to mean water level at Father Point (Pointe au Pere), Quebec, International Great Lakes Datum (1955).

AIDS TO NAVIGATION. Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

SYMBOLS AND ABBREVIATIONS. For complete list of symbols and abbreviations see Chart No. 1.

AUTHORITIES. Hydrography and topography by the National Ocean Service, Charting and Geodetic Services with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

BRIDGE AND OVERHEAD CABLE CLEARANCES. When the water surface is above Low Water Datum, bridge and overhead clearances are reduced correspondingly. For clearances see U.S. Coast Pilot 6.

SAILING DIRECTIONS. Bearings of sailing courses are true and distances given thereon are in statute miles between points of departure.

CAUTION
POTABLE WATER INTAKE (PWI)

Vessels operating in fresh water lakes or rivers shall not discharge sewage, or ballast, or bilge water within such areas adjacent to domestic water intakes as are designated by the Surgeon General (21 CFR 1250.93). Consult U.S. Coast Pilot 6 for important supplemental information.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 6 for important supplemental information.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 6. Additions or revisions to Chapter 2 are published in the Notices to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 9th Coast Guard District in Cleveland, Ohio, or at the Office of the District Engineer, Corps of Engineers in Buffalo, New York.

Refer to charted regulation section numbers.

NOAA VHF-FM WEATHER BROADCASTS

The National Weather Service station listed below provides continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.

Erie, Penn. KEC-58 162.40 MHz (Chan. WX-2)

NOTE B

The channel legend reflects the Corps of Engineers project depth. The Corps of Engineers publishes the controlling depth periodically in the U.S. Coast Guard Local Notice to Mariners. For further information on channel depths, direct inquiries to Office of the District Engineer, Corps of Engineers, Buffalo, N.Y.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Notice to Mariners.

During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

CAUTION

Only marine radiobeacons have been calibrated for surface use. Limitations on the use of certain other radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and Defense Mapping Agency Publication 117.

Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.

Station positions are shown thus:

⊙(Accurate location) o(Approximate location)

CAUTION

Due to periodic high water conditions in the Great Lakes, some features charted as visible at Low Water Datum may be submerged, particularly in the near shore areas. Mariners should proceed with caution.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot 6 for details.

Low Water Datum, which is the plane of reference for the levels shown on the above hydrograph, is also the plane of reference for the charted depths. If the lake level is above or below Low Water Datum, the existing depths are correspondingly greater or lesser than the charted depths.

LOGARITHMIC SPEED SCALE

1 2 3 4 5 6 7 8 9 10 15 20 25 30 40 50 60

To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.0 nautical miles run in 15 minutes, the speed is 16.0 knots

FEET

100 0 1 2 3 4 500 6 7 8 9 1000 1500 2000

METERS

100 50 0 100 200 300 400 500 600

STATUTE MILES

0 1 2 3 4 5

SOUNDINGS IN FEET

25th Ed. Sept. 29/90 ■
14836

C55.418/7:14836/990

CAUTION

This chart has been corrected from the Notice to Mariners published weekly by the Defense Mapping Agency Hydrographic/Topographic Center and the Local Notice to Mariners issued periodically by each U.S. Coast Guard district to the date shown in the lower left hand corner.

20th Anniversary 1970-1990
National Oceanic and Atmospheric Administration
"Serving The Nation"
John A. Knauss Administrator

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE

FATHOMS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
FEET	6	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102

METERS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

(Ashtabula Harbor)
SOUNDINGS IN FEET - SCALE 1:5,000

14836

DMA STOCK NO. 14XHA14836